

MAFLEX

ETHON 30/30

ETHON 35/40



ETHON

Ethon 30/30 and Ethon 35/40 are both available in Double Embossing/Laminating configuration or in Double Embossing configuration.

Furthermore we are able to offer a wide range of rubber to steel and steel to steel embossing units upon specific request.



Technical Data Sheet

	ETHON 30/30	ETHON 35/40
Mechanical speed	650 mt/min	650 mt/min
Guaranteed speed without glue	600 mt/min	600 mt/min
Guaranteed speed with glue	300 mt/min	400 mt/min
Steel roll diameter	300 mm	350 mm
Rubber roll diameter	350 mm	380 mm
Steel rolls lubrication system	Yes	Yes
Standard engraving	Yes	Yes
Automatic paper web passage	No	Yes
Installed power	80 Kw	80 Kw
Air consumption at 6 bar	150 lt/min	150 lt/min
Color	R.A.L. 1013	R.A.L. 1013

- Double Embossing/Laminating unit may be easily turned into a simple double embossing unit excluding the laminator section just opening it.
- Our tanks for glue are designed and engineered for easy removal and maintenance.
- Upon request we can equip the unit with a system able to detect dysfunctional vibrations of the embosser/laminator.



PARTNERS

AC&T Ltd.
12 Woolwell Drive – Plymouth
PL6 7JP – ENGLAND
Phone +44 (0)1752 795 633
Fax +44 (0)1752 795 633

MAFLEX

Tel. +39 0583 316820
Fax +39 0583 318772
Viale S. Concordio - Trav. III, n.199
55100 LUCCA - Italy
e-mail: info@maflex.it